



Span-Rite® Adjustable Steel Frames

While offering the strength and security expected from a Masonite® product, Span-Rite® allows for quick installation and maximum adjustability for varying wall thicknesses that might otherwise be difficult. The two-piece design saves time by installing into the opening as a prehung unit in approximately 30 minutes. Span-Rite is a UL Listed,* fire rated door frame.



Span-Rite®

Adjustable Steel Frame

Span-Rite® is a fast-installing, 18-gauge steel frame, offered in six sizes for jamb widths from 4-1/8" to 7-1/8" (wider widths are available upon request). Two-piece design allows up to 1/2" adjustability for varying wall thicknesses. Span-Rite is available with 90-minute UL Listed* fire rating.

Selection Guide

All Span-Rite frames are available in either right or left hand, in-swing/out-swing and in the following widths and heights. The universal deadbolt strike prep allows for deadbolt prep at 3-5/8", 4", 5-1/2", or 6" above lock strike.

Select frame by wall size

Frame	Wall size
SR-1	4-1/8" – 4-9/16"
SR-2	4-5/8" – 5-1/16"
SR-3	5-1/8" – 5-9/16"
SR-4	5-5/8" – 6-1/16"
SR-5	6-1/8" – 6-9/16"
SR-6	6-5/8" – 7-1/8"

Applications

- House to garage
- Exterior door from garage
- Front entry for security
- Corridor openings – multi-family installations requiring fire ratings
- Motel/Hotel room entry – exterior or interior
- Remodeling projects – minimum rework of existing openings

Features

- 18-gauge primed steel inner section (also available in 16-gauge) – Includes 90 minute UL Listed* fire rating stamp
- 24-gauge outer section (also available in 20-gauge)
- Frame prepared for 4" non-template hinges
- Frame prepared for 2-1/4" full lip strike with universal deadbolt prep (optional mortise strike available)

*Underwriters Laboratories, Inc.